



Conversion Process of a Ballistic Research Laboratory Computer-Aided Design (BRL-CAD) Model to a Panelized Surface Model (PSM)

by Robert W. Kunkel, Jr.,
and John R. Anderson

ARL-TR-2396

February 2001

Approved for public release; distribution is unlimited.

20010320 038

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21010-5423

ARL-TR-2396

February 2001

Conversion Process of a Ballistic Research Laboratory Computer-Aided Design (BRL-CAD) Model to a Panelized Surface Model (PSM)

by Robert W. Kunkel, Jr., and John R. Anderson
Survivability/Lethality Analysis Directorate

Abstract

As the Department of Defense (DOD) develops new Survivability/Lethality and Vulnerability (SLV) analysis models, Ballistic Research Laboratory Computer-Aided Design (BRL-CAD) becomes an integral part in completing the task. BRL-CAD is very adaptable at creating new tools with little effort. These tools will assist us in continuing the development of Chemical Agent Deposition Analysis for Rotorcraft Surfaces (CADARS) by allowing the creation of a panelized surface model (PSM) with greater resolution. This PSM conversion methodology may also be utilized by others in the DOD community.

Table of Contents

	<u>Page</u>
List of Figures	v
Executive Summary	vii
1. Introduction	1
1.1 Purpose.....	1
1.2 BRL-CAD Background.....	1
1.2.1 <i>Primitives</i>	2
1.2.2 <i>Regions</i>	2
1.2.3 <i>Subtractions</i>	2
1.2.4 <i>Intersection</i>	2
1.2.5 <i>Union</i>	3
1.3 CADARS Background.....	3
1.4 VTCALC Background.....	3
1.5 LDTRAN Background.....	4
2. Threat	4
3. Scope	4
4. Theory for Supporting PSM Conversion.....	5
5. Implementation.....	7
6. Example.....	7
7. Conclusion.....	7
8. References	17
Distribution List.....	19
Report Documentation Page	23

INTENTIONALLY LEFT BLANK.

List of Figures

<u>Figure</u>		<u>Page</u>
1.	The RAH-66 Comanche Helicopter.....	8
2.	Three-Dimensional Graphical Output Using Color Coding	9
3.	Simplified BRL-CAD Model.....	10
4.	Facetted Shell Representing the Shape of the Simplified Model.....	11
5.	“Exploded” View of CH-47F Shell Produced by the g-shell.rect Program	12
6.	The CH-47D Chinook Helicopter	13
7.	The UH-60L Blackhawk Helicopter	14
8.	The MH-60K Helicopter	15
9.	The Converted CH-47F Chinook Helicopter	16

INTENTIONALLY LEFT BLANK.

Executive Summary

Under contract, the Ballistics and Nuclear, Biological, and Chemical (NBC) Division of the Survivability/Lethality Analysis Directorate (SLAD) of the U.S. Army Research Laboratory (ARL), Aberdeen Proving Ground, MD, had developed a model to analyze rotor-wash* effects on chemical agent deposition for rotorcraft. This model, Chemical Agent Deposition Analysis for Rotorcraft Surfaces (CADARS), was developed by Continuum Dynamics, Inc., Princeton, NJ, under Contract No. DAAL01-95-C-0056. CADARS consists of two major elements: Lagrangian Deposition and Trajectory Analysis (LDTRAN) code and Vortex Trajectory Calculation (VTCALC) program.

The panelized surface model (PSM) is a key item that is utilized by CADARS. This report explains how the PSM is generated from a Ballistic Research Laboratory Computer-Aided Design (BRL-CAD) model and how it is used within CADARS.

A detailed description of the model is presented in the CADARS user's manual.¹ CADARS models a rotorcraft operating in a chemical agent cloud by predicting the airflow around the airframe and using particle trajectory algorithms to determine the chemical agent deposition on the airframe surface. Part of the input for CADARS is defined as a mission profile consisting of speed, height, direction, and time factors. The output from CADARS is defined as surface information at various locations on the panelized airframe. For each panel, airflow velocity vectors, local pressure gradients, and agent deposition rates are determined. The CADARS output is presented either in a tabulated numerical format or as a three-dimensional graphical output using color coding to identify individual panel data.

* Rotor-wash is the wind and vortices caused by the rotor blade moving through the air.

¹ Andrese, J. A., T. Q. Quackenbush, R. M. McKillip, T. B. Curbishley, and M. E. Teske. "Technical Description and User Notes for LDTRAN/CB Code Used in the Chemical Agent Deposition Analysis for Rotorcraft Surfaces (CADARS) Model." ARL-TR-1331, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, May 1997.

The first attempt at the conversion process used a special operations aircraft (SOA). The SOA program modified existing CH-47D Chinook cargo and UH-60A/L Blackhawk utility helicopters for multiservice special operations forces (SOF) missions. The MH-60K, which was derived from the UH-60A/L, was chosen for the conversion.

The RAH-66 Comanche target description was the second description that was converted to a PSM. The Comanche was first developed by Sikorsky Aircraft Company under contract with ARL (see Figure 1). It was created using BRL-CAD's Multidevice Graphics Editor (MGED).

The most recent attempt used the CH-47F Chinook, a next generation CH-47D. This model, along with data supplied by the chemical/biological agent vapor, liquid, and solid tracking (VLSTRACK)² was used to determine the chemical agent deposition on the aircraft.

As the Department of Defense (DOD) develops new Survivability/Lethality and Vulnerability (SLV) analysis models, BRL-CAD becomes an integral part in completing the task. BRL-CAD is very adaptable at creating new tools with little effort. These innovative tools will assist us in continuing the development of CADARS by allowing the creation of a PSM with greater resolution. This PSM conversion methodology may also be utilized by others in the DOD community. For example, a contractor at ITT Systems Corporation, AvIDyne (formerly Kaman Sciences), has already benefited from this effort in performing blast loading on the Longbow Apache.

² Bauer, T. J., and R. L. Gibbs. "Software User's Manual for the Chemical/Biological Agent Vapor, Liquid, and Solid Tracking (VLSTRACK) Computer Model, Version 1.6.3 (Windows)." NSWCDD/MP-97/196, Naval Surface Warfare Center, Dahlgren Division, Dahlgren, VA, September 1997.

1. Introduction

Under contract, the Ballistics and Nuclear, Biological, and Chemical (NBC) Division of the Survivability/Lethality Analysis Directorate (SLAD) of the U.S. Army Research Laboratory (ARL), Aberdeen Proving Ground, MD, had developed a model to analyze rotor-wash* effects on chemical agent deposition for rotorcraft. This model, Chemical Agent Deposition Analysis for Rotorcraft Surfaces (CADARS), was developed by Continuum Dynamics, Inc., Princeton, NJ, under Contract No. DAAL01-95-C-0056. CADARS consists of two major elements: Lagrangian Deposition and Trajectory Analysis (LDTRAN) code and Vortex Trajectory Calculation (VTCALC) program. More details about LDTRAN and VTCALC will be discussed in a later section.

1.1 Purpose. The purpose of this report is to document a process, utilizing newly developed Ballistic Research Laboratory-Computer Aided Design's (BRL-CAD) tools, that convert typical target descriptions into a panelized surface models (PSM). The converted descriptions can then be used as input to chemical agent deposition models used for survivability analyses.

1.2 BRL-CAD Background. The RAH-66 Comanche target description was first developed by Sikorsky Aircraft Company under contract with ARL (see Figure 1). It was created using BRL-CAD's Multidevice Graphics Editor (MGED) [1]. MGED is a program that provides the visual feedback and operator control necessary to build, modify, and validate highly complex geometric models of tanks, aircraft communication vans, etc. Since 1983, ARL has been constructing three-dimensional (3-D) solid models using BRL-CAD's MGED for subsequent use in vulnerability analyses. Approximately 120 target descriptions, both red and blue, have been created using BRL-CAD. The next few sections describe building blocks of BRL-CAD.

* Rotor-wash is the wind and vortices caused by the rotor blade moving through the air.

1.2.1 Primitives. The geometric solids most commonly used in creating a target description are derived from the following primitives: ARbitrary convex polyhedrons (ARB#) with four to eight vertices, ELLipsoids (ELL), TORii (TOR), and Truncated General Conics (TGC). These solids contain a specialized menu-driven parameter manipulation, which permits refined definition of a solid's shape and size. (See Ellis [2] for more details regarding these geometric solids.)

1.2.2 Regions. A geometric solid alone is insufficient in describing the complex shapes encountered in a target description. Combining solids using the three Boolean operators permits the imitation of the shape and form of the intricate objects. The Boolean operators are subtraction, intersection, and union. Boolean operations, which are binary, allow two solids or regions to be paired using the indicated Boolean operator. The result is processed as a new volume to be paired with the next solid and its specific Boolean operator. When Boolean operators are used to define a region, the region becomes a part of the database. A region can be as simple as a single solid or as complicated as hundreds of members combined with Boolean operators.

1.2.3 Subtractions. Subtracting two solids involves all the volume of the first solid less any common volume with the second solid. The subtraction operator (-) signifies subtraction and is useful in hollowing a body, removing an odd-shaped piece of solid, or accounting for edge intersection of walls, plates, piping, or other connected solids. One important restriction of the Boolean use that must be accommodated is the convention that regions must begin with a positive body. If an initial solid within a region is associated with the subtraction operator, the subtraction is ignored and the union operator is substituted.

1.2.4 Intersection. The intersection operation (+) combines two solids, saving only their common value. Unusual shapes can be attained using this operator; it is commonly used to save a piece of a shell, as in a radar dish, or to use only a portion of a standard primitive in a component's definition. Intersection between two solids having no common points would be the null set, which is a region having no evaluation potential.

1.2.5 Union. The concept of union is the converse of intersection. The union operator (u) joins solids so that any volume in at least one is part of the resulting volume. The union operation allows several related parts of a single component overlapping or trailing one after another to be defined in one region. Usefulness of the union operation is typified in creating wiring harnesses or fuel and hydraulic lines. For further details and insight into the target description process, see Ellis [2].

1.3 CADARS Background. The CADARS model was developed by Continuum Dynamics, Inc., Princeton, NJ, under contract with ARL. A detailed description of the model was presented in the CADARS user's manual [3]. CADARS models a rotorcraft operating in a chemical agent cloud by predicting the airflow around the airframe and using particle trajectory algorithms to determine the chemical agent deposition on the airframe surface. Part of the input for CADARS defines a mission profile consisting of speed, height, direction, and time factors. The output from CADARS is defined as surface information at various locations on the panelized airframe. For each panel, airflow velocity vectors, local pressure gradients, and agent deposition rates are determined. The CADARS output is presented either in a tabulated numerical format or as a 3-D graphical output using color coding to identify individual panel data (see Figure 2).

1.4 VTCALC Background. The first class of issues addressed in the development of CADARS involved basic features of the modeling of the rotor wake. The appropriate level of modeling for current purposes was assessed through extensive test calculations of predicted flow fields at key points near the rotor, with the goal of achieving a time-reduced computational burden. The best balance of accuracy and efficiency was achieved with a wake model consisting of two free vortex filaments trailing from each blade. The new wake model was embodied in a focused set of routines whose primary task was computing the geometry of the vortex wake of the rotor and its resultant velocity field. This software, designated the VTCALC Program, was used as a preprocessor for the LDTRAN.

1.5 LDTRAN Background. The coupled effect of the body, the body and its wake, and (when appropriate) the ground were computed on a volumetric grid of points and around the aircraft; a time-averaged flow field was then computed. (Time averaging was invoked since the flow field around a rotor was periodic with a period of 0.05 s; fluctuations on this time scale were short enough to be averaged for droplet transport.) The flow field was then used to convert an array of droplets from starting positions on the boundary of the computational grid until they either impacted on the fuselage surface or encountered another boundary of the grid. Using efficient interpolation and numerical integration schemes adapted from the FSCBG/AGDISP* code, droplet trajectories were generated for each of the user-selected mission segments and chemical agents. The distances between the droplet trajectories and the panel centroids were then used in an interpolation scheme to compute the effective collection rate (mass/time) on each panel surface for each flight condition. Total accumulation on a panel was computed by scaling the collection rate by the total duration of exposure to a particular ambient concentration of the chemical agent in question. For further details regarding the two primary elements of CADARS, see Andrese [3].

2. Threat

While this conversion method is being used in several chemical agent challenge analyses, it is independent of threat.

3. Scope

CADARS uses a PSM, which is a 3-D computerized replication of the exterior airframe. The PSM is achieved by converting a BRL-CAD target description. The following sections will discuss the conversion process in detail.

* FSCBG/AGDISP = Forest Service Crame-Barry Grim and Agricultural Dispersal.

4. Theory for Supporting PSM Conversion

The first step in the conversion process is to modify the BRL-CAD target description to resemble the desired PSM. The most successful approach is modifying the BRL-CAD model to obtain the basic shape of the aircraft body with no openings to the interior and no holes through the body. CADARS does not calculate, at this time, any interior airflow, therefore all windows, doors, engine inlets, exhaust ducts, openings for the main rotor mast, and openings for the fan-in-fin must be closed. Exterior details such as antennae, landing gear and skids, and missile pylons should also be removed. Figure 3 depicts the Comanche in the mode just described. The interior components of the BRL-CAD model may be removed to improve processing time for the conversion, but is not necessary. Once the simplified BRL-CAD model is completed, a faceted shell representing the shape of the simplified model is created (see Figure 4). The two newly created BRL-CAD tools available for this part of the process are the `g-shell.radial` and the `g-shell.rect`. Both produce a single faceted shell in the form of an n-Manifold Geometry (NMG) solid by raytracing the simplified BRL-CAD model. These two newly developed tools are now part of the latest release of BRL-CAD.

The `g-shell.radial` program shoots rays from the perimeter of a series of circles with centers inside the BRL-CAD model. The points where each ray first intercepts the model are vertices of the PSM. The user provides a series of circle centers and a distance increment. The code interpolates between the specified centers and a distance increment. The code then linearly interpolates between the specified centers to produce a series of centers that are spaced at the specified distance increment. The user also specifies an angular increment of which to set the density of the rays fired around each circle. All the circles are oriented in the same direction (in parallel planes), user specified as the x, y, and z directions. This code is best applied to aircrafts with cylindrical-shaped bodies.

The `g-shell.rect` program begins by shooting rays in the y-direction on a uniformly spaced grid. Using this information, it then builds a crude shell. This shell is refined by using information obtained by shooting rays in the x and z directions. The user specifies the grid

spacing. The first shell created by this code will be two surfaces (consisting of the first and last ray intercepts) connected by straight lines in the y direction. The refining process adjusts the straight lines to more closely match the actual shape. This allows the process to consider recesses and subtle curvatures that the original raytracing in the y direction did not detect. The g-shell.rect code is generally more robust than the g-shell.radial but will require more computational time. (See Figure 5.)

The g-shell.rect and g-shell.radial should first be used to create the basic NMG shell. Any details added to the basic shell should be converted to NMGs separately using the same two tools. Details such as wings, pylons, horizontal stabilizers, and vertical stabilizers may be added in this manner. The question arises as to whether a part should be included with the main shell or added later as a detail. Some guidelines include the following:

- If the size of the part is about the size of the grid spacing or has a thickness on the x or z direction that is of the same order, then it should be converted to an NMG separately. Typically, the part may need to be rotated to get its largest presented area facing the y direction; then, the resulting NMG is rotated back to the original position.
- If important recesses cannot be seen from the cardinal views, then the parts that create those recesses must be converted separately.
- Any holes through the model should be filled and created later. Any remaining holes in the y direction will be represented by holes from the inside surface that are the boundaries of the grid cells and will not be improved by the refining rays. Any holes in the x or z direction will not appear.

After all the parts are converted to NMGs, they may be combined into a single BRL-CAD database file and made into a BRL-CAD region using the Boolean operations previously mentioned. The union operator should be used to join the different pieces, and the subtraction operator should be used to create necessary holes. The region may then be converted to a single

NMG solid using the g-nmg code. This code converts BRL-CAD regions to NMGs by performing the prescribed Boolean operations from the region, resulting in a single faceted NMG shell. This shell can be converted to the required PSM format using the nmg-sgp tool.

5. Implementation

The first attempt at the conversion process used a special operations aircraft (SOA). The SOA Program modified existing CH-47D Chinook cargo and UH-60A/L Blackhawk utility helicopters for multiservice special operations forces (SOF) missions. The MH-60K, which was derived from the UH-60A/L, was chosen for the conversion (see BRL-CAD representations of the CH-47D Chinook and UH-60L Blackhawk helicopters in Figures 6 and 7, respectively). An MH-60K is shown in Figure 8.

6. Example

The most recent attempt used the CH-47F Chinook, a next generation CH-47D. Figure 5 portrays the BRL-CAD model of the Chinook, and Figure 9 depicts the converted CH-47F. This model, along with data supplied by VLSTRACK, was used to determine the chemical agent deposition on the aircraft.

7. Conclusion

As new evaluation models are developed, conversion of the BRL-CAD model becomes an integral part in completing the task. BRL-CAD is very adaptable in creating new tools with little effort. These innovative tools will aid in the development of CADARS by allowing the creation of a PSM with greater resolution. This PSM conversion method can also be utilized by the DOD community. A contractor at ITT Systems Corporation, AviDyne, has already benefited from this effort in performing blast loading on the Longbow Apache.



Figure 1. The RAH-66 Comanche Helicopter.



Figure 2. Three-Dimensional Graphical Output Using Color Coding.




Figure 3. Simplified BRL-CAD Model.




Figure 4. Facetted Shell Representing the Shape of the Simplified Model.




Figure 5. “Exploded” View of CH-47F Shell Produced by the g-shell.rect Program.




Figure 6. The CH-47D Chinook Helicopter.



Figure 7. The UH-60L Blackhawk Helicopter.



Figure 8. The MH-60K Helicopter.




Figure 9. The Converted CH-47F Chinook Helicopter.

8. References

1. Muuss, M. J. (Compiler). "The Ballistics Research Laboratory CAD Package Release 4.0, Volume IV." U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, December 1991.
2. Ellis, C. A. "Vulnerability Analyst's Guide to Geometric Target Description." BRL-MR-4001, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, September 1992.
3. Andrese, J. A., T. Q. Quackenbush, R. M. McKillip, T. B. Curbishley, and M. E. Teske. "Technical Description and User Notes for LDTRAN/CB Code Used in the Chemical Agent Deposition Analysis for Rotorcraft Surfaces (CADARS) Model." ARL-TR-1331, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, May 1997.

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFORMATION CENTER DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218	1	DIRECTOR US ARMY RESEARCH LAB AMSRL DD 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	HQDA DAMO FDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460	1	DIRECTOR US ARMY RESEARCH LAB AMSRL CI AI R (RECORDS MGMT) 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	OSD OUSD(A&T)/ODDDR&E(R) R J TREW THE PENTAGON WASHINGTON DC 20301-7100	3	DIRECTOR US ARMY RESEARCH LAB AMSRL CI LL 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DPTY CG FOR RDA US ARMY MATERIEL CMD AMCRDA 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001	1	DIRECTOR US ARMY RESEARCH LAB AMSRL CI AP 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	INST FOR ADVNCD TCHNLGY THE UNIV OF TEXAS AT AUSTIN PO BOX 202797 AUSTIN TX 78720-2797		<u>ABERDEEN PROVING GROUND</u>
1	DARPA B KASPAR 3701 N FAIRFAX DR ARLINGTON VA 22203-1714	4	DIR USARL AMSRL CI LP (BLDG 305)
1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE MADN MATH MAJ HUBER THAYER HALL WEST POINT NY 10996-1786		
1	DIRECTOR US ARMY RESEARCH LAB AMSRL D D R SMITH 2800 POWDER MILL RD ADELPHI MD 20783-1197		

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	OASD C3I MR BUCHHEISTER RM 3D174 6000 DEFENSE PENTAGON WASHINGTON DC 20310-6000	1	OADCSOPS FORCE DEV DIR DAMO FDZ ROOM 3A522 460 ARMY PENTAGON WASHINGTON DC 20310-0460
1	OUSD AT STRT TAC SYS DR SCHNEITER RM 3E130 3090 DEFENSE PENTAGON WASHINGTON DC 20310-3090	1	HQDA ODCSPER DAPE MR (RM 2C733) 300 ARMY PENTAGON WASHINGTON DC 20310-0300
1	OUSD AT S&T AIR WARFARE RM 3E139 R MUTZELBUG 3090 DEFENSE PENTAGON WASHINGTON DC 20301-3090	1	US ARMY MATERIEL CMD DEP CHF OF STAFF FOR RDA SCIENCE TECH ENG AMCRDA 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	OUSD AT S&T LAND WARFARE RM EB1060 A VIIIU 3090 DEFENSE PENTAGON WASHINGTON DC 20310-3090	1	US ARMY MATERIEL CMD DEP CHF OF STAFF FOR RDA SCIENCE TECH ENG AMCRDA T 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	UNDER SEC OF THE ARMY DUSA OR ROOM 2E660 102 ARMY PENTAGON WASHINGTON DC 20310-0102	1	US ARMY ARMAMENT RDEC AMSTA AR TD M FISETTE BLDG 1 PICATINNY ARSENAL NJ 07806-5000
1	ASST SECY ARMY ACQUISITION LOGISTICS TCHNLGY SARD ZD ROOM 2E673 103 ARMY PENTAGON WASHINGTON DC 20310-0103	1	ECBC AMSSB RTD J ZARZYCKI 5183 BLACKHAWK RD APG MD 21010-5424
1	ASST SECY ARMY ACQUISITION LOGISTICS TCHNLGY SARD ZP ROOM 2E661 103 ARMY PENTAGON WASHINGTON DC 20310-0103	1	US ARMY MISSILE RDEC AMSMI RD W MCCORKLE REDSTONE ARSENAL AL 35898-5240
1	ASST SECY ARMY ACQUISITION LOGISTICS TCHNLGY SAAL ZS ROOM 3E448 103 ARMY PENTAGON WASHINGTON DC 20310-0103	1	NATICK SOLDIER CENTER SBCN T P BRANDLER KANSAS STREET NATICK MA 01760-5056

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	US ARMY TANK AUTOMTV RDEC AMSTA TR J CHAPIN WARREN MI 48397-5000
1	US ARMY INFO SYS ENGRG CMD AMSEL IE TD F JENIA FT HUACHUCA AZ 85613-5300
1	US ARMY SIM TRNG INST CMD AMSTI CG M MACEDONIA 12350 RESEARCH PKWY ORLANDO FL 32826-3726
1	US ARMY TRADOC BATTLELAB INTEGRATION TECH B CONCEPTS DIR ATCD B FT MONROE VA 23561-5000
1	ARMY TRADOC ANL CTR ATRC W MR KEINTZ WSMR NM 88002-5502
1	US ARMY RESEARCH LAB AMSRL SL PLANS AND PGMS MGR WSMR NM 88002-5513
1	US ARMY RESEARCH LAB AMSRL SL E WSMR NM 88002-5513
1	US ARMY RESEARCH LAB AMSRL SL EA R FLORES WSMR NM 88002-5513
1	US ARMY RESEARCH LAB AMSRL SL EM J PALOMO WSMR NM 88002-5513
1	US ARMY RESEARCH LAB AMSRL SL EI J NOWAK FT MONMOUTH NJ 07703-5602

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
	<u>ABERDEEN PROVING GROUND</u>
1	US ARMY DEV TEST COM CSTE DTC TT T APG MD 21005-5055
1	US ARMY EVALUATION CENTER CSTE AEC SV D DELATTRE 4120 SUSQUEHANNA AVE APG MD 21005-3013
1	US ARMY RESEARCH LAB AMSRL SL BN D FARENWALD APG MD 21010-5423
2	US ARMY RESEARCH LAB AMSRL SL DR WADE J BEILFUSS
4	US ARMY RESEARCH LAB AMSRL SL B MS SMITH J FRANZ M VOGEL W WINNER
1	US ARMY RESEARCH LAB AMSRL SL BA M RITONDO
1	US ARMY RESEARCH LAB AMSRL SL BD J MORRISSEY
2	US ARMY RESEARCH LAB AMSRL SL BE D BELY R SANDMEYER
1	US ARMY RESEARCH LAB AMSRL SL BG A YOUNG
1	US ARMY RESEARCH LAB AMSRL SL E M STARKS

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

1 US ARMY RESEARCH LAB
 AMSRL SL EA
 D BAYLOR

1 US ARMY RESEARCH LAB
 AMSRL SL EM
 J FEENEY

1 US ARMY RESEARCH LAB
 AMSRL SL EC
 E PANUSKA

NO. OF
COPIES ORGANIZATION

1 US ARMY AVIATION RESEARCH
DEVELOPMENT AND ENG CENTER
AMSAM AR N J KIRKWOOD
BLDG 5678 RM 56
REDSTONE ARSENAL AL 35898-5000

1 US ARMY AVIATION RESEARCH
DEVELOPMENT AND ENG CENTER
AMSAM RD AS JTR B R MILLER
REDSTONE ARSENAL AL 35898-5000

INTENTIONALLY LEFT BLANK.

REPORT DOCUMENTATION PAGE			<i>Form Approved</i> <i>OMB No. 0704-0188</i>	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE February 2001	3. REPORT TYPE AND DATES COVERED Final, February 1999 - April 2000	
4. TITLE AND SUBTITLE Conversion Process of a Ballistic Research Laboratory Computer-Aided Design (BRL-CAD) Model to a Panelized Surface Model (PSM)			5. FUNDING NUMBERS 665604D670	
6. AUTHOR(S) Robert W. Kunkel, Jr., and John R. Anderson				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-SL-BN Aberdeen Proving Ground, MD 21010-5423			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-2396	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) As the Department of Defense (DOD) develops new Survivability/Lethality and Vulnerability (SLV) analysis models, Ballistic Research Laboratory Computer-Aided Design (BRL-CAD) becomes an integral part in completing the task. BRL-CAD is very adaptable at creating new tools with little effort. These tools will assist us in continuing the development of Chemical Agent Deposition Analysis for Rotorcraft Surfaces (CADARS) by allowing the creation of a panelized surface model (PSM) with greater resolution. This PSM conversion methodology may also be utilized by others in the DOD community.				
14. SUBJECT TERMS panelized surface model, CADARS, BRL-CAD, Army aircraft, rotorwash			15. NUMBER OF PAGES 29	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

- 1. ARL Report Number/Author ARL-TR-2396 (Kunkel) Date of Report February 2001
- 2. Date Report Received _____
- 3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

- 4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

- 5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

- 6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name E-mail Name

Street or P.O. Box No.

City, State, Zip Code

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)